

Safety Data Sheet

Sodium Hydroxide 50%

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND SUPPLIER

Product Name
Recommended Uses
Supplier
Supplier
Street address
Sodium Hydroxide 50%
Food industry cleaner
Hygiene Technologies Ltd
28 Rangitane Road Hastings

**Telephone Number** (06) 876 4111

Emergency Telephone NZ Fire Service - 111

National Poisons Centre - 0800 764 766 (0800 POISON)

2. HAZARDS IDENTIFICATION

**Dangerous Goods** This product is classified as a Dangerous Good according to NZS 5433:2020

Transport of Dangerous Goods on Land

Hazardous Substances Classified as hazardous according to criteria in GHS 7

GHS Skin Corrosion – Category 1B

Serious Eye Damage – Category 1 Acute Toxicity (Oral) – Category 4

SIGNAL WORD DANGER

Pictograms Corrosion, Exclamation Mark

Group Standard 2020 HSR002526

Hazard Statements H314 Causes severe skin burns and eye damage.

H302 Harmful if swallowed.

**Precautionary Statements** 

Prevention

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions. P260 Do not breathe fumes, mist, vapours or spray.

P264 Wash hands, face and all exposed skin thoroughly after handling.

H270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves and protective clothing including eye and face

protection.

**Response** P101 If medical advice is needed, have product container or label at hand.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P301+P312 IF SWALLOWED: Call a POISON CENTRE or doctor if you feel

unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water or shower. P363 Wash contaminated clothing before reuse.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

oreathing

P310 Immediately call a POISON CENTRE or doctor. P321 Specific treatment (see Section 4 of this SDS).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Date of Issue: 14/03/2025

Remove contact lenses, if present and easy to do. Continue rinsing.

Storage P405 Store locked up.

**Disposal** P501 Dispose of contents and container in accordance with local, regional, national

and international regulations.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Proportion % (w/w)
Sodium hydroxide	1310-73-2	30 – 60
Ingredients classified as non-hazardous at		Balance
the concentrations used.		

## 4. FIRST AID MEASURES

For advice, contact National Poisons Information Centre (Phone 0800 764 766) or a doctor If medical advice is needed, have product container or label at hand.

**Swallowed** Rinse mouth and then drink a glass of water. Do <u>NOT</u> induce vomiting. Never

give anything by mouth to an unconscious person. If vomiting occurs, give further water. Immediately call a POISON CENTRE or doctor for advice. Immediately rinse cautiously with copious volumes of water for 15 minutes,

holding eyelids open and occasionally lifting the upper and lower lids. Remove contact lenses, if present and easy to do. Continue rinsing. Urgently transport

to hospital or medical centre without delay.

Skin Contact If skin or hair irritation occurs, remove all contaminated clothing and flush skin and

hair with running water for at least 15 minutes. For minor skin contact, avoid spreading material on to unaffected skin. If swelling, redness, blistering or irritation occurs seek medical attention. For gross contamination, immediately drench contaminated skin and clothing with plenty of water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is soluble). For skin burns, cover with a clean, dry dressing until medical help is available. Immediately call a POISON CENTRE or doctor for advice. Wash contaminated clothing before

reuse.

**Inhaled** Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a Poison Centre or doctor for advice. Allow person to assume most comfortable position and keep at rest until fully recovered. Seek medical

assistance if effects persist.

Refer to National Poisons and Hazardous Chemicals Information Centre 0800 764 766.

## 5. FIRE-FIGHTING MEASURES

**Specific Hazard** Corrosive liquid. Non-combustible material.

Suitable Extinguishing Media If material is involved in a fire, use fine water spray, standard foam or dry agent

(carbon dioxide, dry chemical powder).

Fire/Explosion Hazards Non-combustible, however following evaporation of aqueous component, residual

material can decompose in involved in a fire, emitting toxic fumes. If safe to do so, remove containers from path of fire. Fire fighters to wear self-contained breathing apparatus (SCBA) and suitable protective clothing if risk of exposure to products of

Date of Issue: 14/03/2025

decomposition.

Hazchem Code 2R

**Eye Contact** 

# 6. ACCIDENTAL RELEASE MEASURES

Contain minor spills from local drainage with any suitable bund or barrier. Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of dusts, mists or sprays. Soak up spilled product using absorbent, non-combustible material such as earth or sand. Avoid using sawdust or cellulose. When saturated, collect material into suitable, clearly labeled, dry, sealable containers and hold for safe disposal. Once clean up is complete, flush spill site with plenty of water to eliminate any residue.

For large spills from drums and IBCs, alert the local Fire Brigade. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination. Ensure adequate ventilation. Work up wind or increase ventilation. Do not touch or walk through spilled material. Avoid contact with skin and eyes. Stop leak if safe to do so. Prevent entry into waterways, drains or confined areas. Use absorbent (earth, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If material contaminates crops, sewers or waterways, alert local emergency services.

## 7. HANDLING AND STORAGE

Handling advice Before use, carefully read the product label. Avoid contact with eyes and skin. Do

not breathe fumes, mist, vapours, spray or dusts (from dried product). Wear protective gloves, protective clothing and eye and face protection (see Section 8).

Contaminated work clothing should not be allowed out of the workplace.

Storage advice Store in a cool, dry and well-ventilated area away from direct sunlight, heat

sources, incompatible materials (described in Section 10) and food stuffs. Ensure containers are correctly labelled, protected from physical damage, sealed when not in use and stored upright. Check containers regularly for leaks and spills. Keep out of reach of children. Store in original packaging as approved by manufacturer. Do not store in aluminium or galvanised containers nor use die-cast zine or aluminium bungs. Plastic bungs should be used. At temperatures greater than 40°C, tanks must be stress relieved. Do not use empty containers for the storge of foodstuffs.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Workplace Exposure Guidelines**

National occupational exposure limits:

TWA STEL NOTICES

ppm mg/m3 ppm mg/m3

Sodium hydroxide Ceiling 2mg/m<sup>3</sup>

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average

airborne concentration of a substance calculated over an eight-hour

working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not

be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-

minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60

minutes between successive exposures in this range.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed

during product manufacture.

Biological Limit Values As per the WorkSafe New Zealand the ingredients in this material do not

have a biological limit allocated.

**Engineering Controls**Use only in well-ventilated areas. Ensure natural ventilation is adequate under normal use conditions and that air concentrations of components

are controlled below Exposure Standards. If an inhalation risk exists, use with local exhaust ventilation or while wearing appropriate respirator.

Date of Issue: 14/03/2025

### **Personal Protective Equipment**

OVERALLS, CHEMICAL GOGGLES, GLOVES, RUBBER BOOTS, FACE SHIELD. APRON

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by a risk assessment.

Wear overalls, chemical goggles, gloves, rubber boots, a face shield and an apron. A face shield can be used for supplementary protection of the face, however never for primary protection of the eyes. If risk of inhalation exists, wear an appropriate respirator meeting the requirements of AS/NZS 1715 and AS-NZS 1716. Available information suggests that gloves made from butyl rubber, natural rubber, nitrile rubber, neoprene and PVC should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. When handling do not eat, drink or smoke. Wash contaminated clothing and other protective equipment before storage or reuse. Ensure that eyewash stations and safety showers are close to the workstation location.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear Liquid Odour Neutral

Colour Clear, slightly pale yellow

Solubility Soluble in water Specific Gravity 1.48 – 1.52 @ 20°C

Flash Point (°C) N App pH >14

Freezing Point Approx. 12°C
Boiling Point >100°C
Vapour Pressure N Av
Viscosity N Av

# 10. STABILITY AND REACTIVITY

Stability This material is thermally stable when stored and used as directed.

**Conditions to avoid** Elevated temperatures and incompatible materials

**Incompatible materials** Acids, ammonium salts, aluminium, tin and zinc

Reactivity Reacts violently with acids. Reacts exothermically on dilution with water. Contact

with metals may liberate hydrogen gas, which is extremely flammable.

**Hazardous Decomposition** 

**Products** 

May evolve toxic fumes when heated to decomposition.

#### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Inhaled** Material may be corrosive to mucous membranes and respiratory tract.

**Skin Contact** Corrosive to skin. Contact with skin will result in severe burns.

Swallowed Harmful if swallowed. Swallowing can result in nausea, vomiting, diarrhoea,

abdominal pain and chemical burns to the gastrointestinal tract.

Eye Contact Corrosive to eyes. Contact with eyes will result in serious eye damage

including redness, pain, blurred vision and severe corneal burns.

Date of Issue: 14/03/2025

Contamination of eyes can result in permanent injury.

**Long Term Effects** No information available for the product.

**Acute Toxicity** Inhalation: This material has been classified as non-hazardous.

**Skin contact:** This material has been classified as non-hazardous.

Ingestion: This material has been classified as a Category 4 Hazard. Harmful if

swallowed.

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Causes serious eye damage. Skin: this material has been classified as a Category 1B Hazard (irreversible effects to skin). Causes

severe skin burns.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser. **Aspiration hazard:** This material has been classified as non-hazardous. **Specific target organ toxicity (single exposure):** This material has been

classified as non-hazardous.

**Chronic Toxicity Mutagenicity:** This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as a Category 2 Hazard. May cause damage to organs through prolonged or

repeated exposure.

# 12. ECOTOXICOLOGICAL INFORMATION

Aquatic toxicity Harmful to aquatic life due to high pH. Avoid contaminating waterways.

**Ecotoxicity** No information available

Persistence/Degradability No information available

Bioaccumulation Potential No information available

**Mobility** No information available

## 13. DISPOSAL

Recycle wherever possible. Whatever cannot be saved for recovery or recycling should be sent to an approved waste disposal contractor for disposal in an approved waste facility. Processing, use or contamination of this product may change the waste management options. Dispose of container and unused contents using an approved waste disposal contractor. Care should be taken to ensure compliance with national and local regulations. This product is NOT for unauthorised disposal by either landfill or via municipal sewers. Not to be discharged to drains, natural streams or rivers.

**Special Precautions:** Empty drums should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Observe all safeguards on label and in this SDS until container is cleaned, reconditioned or destroyed. Decontaminate empty containers with water. Dispose of container and unused contents in accordance with local authority requirements.

# 14. TRANSPORT INFORMATION

### **Transport of Dangerous Goods Pictograms:**

Classified as a Dangerous Good according to NZS 5433:2020 Transport of Dangerous Goods on Land.

## **Road and Rail Transport**

UN No:1824Dangerous Goods Class:8Packing Group:IIHazchem Code:2REmergency Response Guide No154



Date of Issue: 14/03/2025

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), radioactive substances (Class 7) or food and food packaging in any quantity. Note 1: Concentrated strong alkalis are incompatible with concentrated strong acids. Note 2: Concentrated strong acids are incompatible with concentrated strong alkalis. Note 3: Acids are incompatible with Dangerous Goods of Class 6 which are cyanides. Exemptions may apply.

Marine Transport Classified as Dangerous Goods by the criteria of the International Maritime

Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1824
Dangerous Goods Class: 8
Packing Group: ||

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Air Transport Classified as Dangerous Goods by the criteria of the International Air Transport

Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1824
Dangerous Goods Class: 8
Packing Group: ||

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION



Date of Issue: 14/03/2025

# 15. REGULATORY INFORMATION

ERMA (NZ) Approval Code N/A

**Group Standard 2020** HSR002526 – Cleaning Products (Corrosive) Group Standard 2020

For more information refer to the ERMA website: www.epa.govt.nz

#### **16. OTHER INFORMATION**

Revision 2

**Revision Date** 14 March 2025

Reason for Issue Regular review

Review 14 March 2030

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond seller's control. The User is responsible to evaluate all available information when using the product for any particular use and to comply with all the current legislation.